



## Kit line-TCPRS1/2xM-20I

Kit line-TCPRS1/2xM-20I, Pulse and contact centraliser

Code: M62520.

- > Protocol: ModbusTCP | TCP | UDP
- > Módulos: 9
- > Communications: Ethernet | WiFi
- > Digital inputs: 40

### Description

Pulse centralizing device to fully manage the consumption of any installation. It can send data to a higher-level SCADA system thanks to the **line-TCPRS1** gateway, which incorporates Wi-Fi and Ethernet communications.

### Application

Manage consumption in:

- Shopping centres
- Flats
- Industry
- Ports and campgrounds



## Kit line-TCPRS1/2xM-20I

Impulse centralizer kits

Code: M62520.

### Specifications

#### AC power supply

Installation category	CAT III 300 V
Consumption	10,5 ... 14,5 VA
Frequency	50 ... 60 Hz
Nominal voltage	100 ... 264 V ~

#### DC power supply

Installation category	CAT III 300 V
Consumption	9 ... 9,5 W
Nominal voltage	100 ... 300 Vdc

#### Mechanical characteristics

Size (mm) width x height x depth	157.5 x 118 x 70 (mm)
Envelope	Self-extinguishing V0 plastic
Fastening	DIN rail
Weight (kg)	0,43

#### Environmental characteristics

Protection class	IP30, Front: IP40
Relative humidity (without condensation)	5 ... 95%
Storage temperature	-20 ... +70 °C
Working temperature	-10 ... +50 °C

#### Communications

Connection mode to Network	DHCP ON/OFF (ON by default)
Band	2,4 GHZ.
Fieldbus	RS-485 / RS-232
Connector	RJ-45
Protocol	TCP / UDP / Modbus TCP / Web server - HTTP / REST
Type	RS-485 / RS-232 / Ethernet / WiFi / Bluetooth
Speed	Ethernet 10 /100 BT (Mbit/s), Modbus: 4800-9600-19200-38400-57600-115200
Standards	IEEE 802.11 b / g , IEEE 802.11 n (hasta 150 Mbps)
Maximum output power	IEEE 802.11 b: 20 dBm / IEEE 802.11 n: 14 dBm
Connection mechanism	Ethernet 10BaseT / 100BaseTX autodetectable Wi-Fi
Technology	Ethernet, WiFi, Bluetooth 4.2 + EDR, Bluetooth LE

#### Standards

Electrical safety, Maximum height (m)	2000
Electrical safety, Installation category	CAT III 300V



## Kit line-TCPRS1/2xM-20I

Impulse centralizer kits

Code: M62520.

Standards

UNE-EN 61010-1, UNE-EN 61000-6-2, UNE-EN 61000-6-4

### User interface

LED

49 LED

### Digital inputs

Input/output insulation

4,2 kVdc

Quantity

40

Consumption (per input)

60 mA inputs OFF / 240 mA inputs ON

Type

Optocoupled

### Kit Line-TCPRS1/M

Impulse and contact centralisers

CODE	TYPE
M62510.	Kit line-TCPRS1/M-20I
M62520.	Kit line-TCPRS1/2xM-20I



## Kit line-TCPRS1/2xM-20I

Impulse centralizer kits

Code: M62520.

### Dimensions

